

CB-3011



FLIR *Ariel*[™]

720p Bullet Camera

The Ariel CB-3011 series of HD 720p cameras has expanded to include an IR illuminated video quality camera that guarantees frame rates in high motion, complex and low light scenes, and lowers your utility costs and carbon footprint.

Through its motion processing architecture, the CB-3011 series delivers predictable storage and a reduction in your Total Cost of Ownership (TCO).

Now you can...deploy a CCTV HD H.264 720p surveillance solution that easily handles wide variations in motion and lighting found in airports, city surveillance projects, critical infrastructure sites, commercial offices and campuses utilizing the most technologically advanced HD IP camera.

- HD H.264 Video
- Multi-streaming at the highest frame rates
- HD 720p at the lowest bit rate
- Included analytics: - Tamper Detection - Multi-zone VMD
- Wide Dynamic Range
- IR Illumination
- Indoor/Outdoor
- Web interface for viewing and configuration

Features

- Multi-stream H.264 video
- Guaranteed frame rates in complex, high motion scenes
- Motion processing
- Auto-tune technology
- IR model delivers more uniform high quality illumination

Benefits

- Crisp, clean video for supreme identification
- Maintains evidentiary integrity of video in challenging surveillance conditions
- Maintains lowest bit rates regardless of motion/scene complexity; lowers TCO with predictable storage and network requirements
- Best out-of-the-box experience with no adjustments; auto scene adaptation eliminates service calls
- Reduces utility costs, carbon footprint and TCO

General Specifications

Camera	
Image Sensor	1/3" CMOS
Sensor Resolution	1280 x 960
Scanning Mode	Progressive
Sensitivity	0.15 (color)/0.02 (BW), 0 Lux with IR illuminator ON, measured at 30 IRE
Lens Type	4 mm F2.0 Auto Iris D/N Horizontal viewing angle: 73.1°
Rotate Options	Mirror and Flip
Automatic Electronic Shutter (AES)	1.0 to 1 / 10,000 (auto)
Digital Slow Shutter (DSS)	1/1 to 1/25 or 1/30 with up to 32x sensitivity boost in color or night mode
White Balance	Auto / indoor / outdoor
Automatic Gain Control (AGC)	Auto
Back Light Compression	Yes
Iris Control	DC Auto
Wide Dynamic Range (WDR)	Digital
3D Noise Reduction	Yes
Tamper Detection	Yes
Privacy Zones	Yes
Video Motion Detection	Yes
Day / Night Mode	Yes
Mechanical IR Cut Filter	Yes
Signal to Noise Ratio (SNR)	±50 dB
Video	
Compression	Fully compliant multi-stream H.264 main profile + MJPEG
Maximum Performance	H.264 30 / 25 @ 1280x960/HD720p + H.264 30 / 25 @ 4CIF
Resolution Range	Scalable from CIF to 1.3MP
Bandwidth	Configurable between 64Kbps and 8Mbps
Rate Control	CBR/VBR
IR Illuminator	
Distance	20 m (66 ft.)
Angle of Illumination	Full 90°
Number of IR LEDs	30
Peak Emission Wavelength (nm)	850
Network	
Network Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6
Ethernet	10 / 100 Base-T auto sensing, half / full duplex (RJ45)
Configuration	Remote: via web access or supported video management software
Firmware Upgrade	Flash memory for upgrade of camera firmware over the network (1GB Flash / 2GB RAM)
Supported Web Browser	Internet Explorer 6.0+
Security	User account and password protection
Physical	
Enclosure	Indoor/Outdoor
Dimensions	60.4 x 76.9 x 139.2 mm (2.38 x 3.28 x 5.48 in.)
Unit Weight	0.5kg (1.1 lbs.)
Electrical	
Input Voltage	12 VDC ±10% or 802.3af PoE
Power Consumption	5W / 7W with IR on
Power Connector	DC barrel connector or PoE
Environmental	
Operating Temperature*	-30°C to 60°C (-22°F to 140°F)
Storage Temperature	-40° to 70° C (-4° to 158° F)
Humidity	95% (non-condensing)

Warranty & Regulatory	
Warranty	According to DVTEL RMA Policy and Process Notice document
USA	UL, FCC Part 15 (subpart B, class A)
International	CE marked, EN55022-1998 class A, EN55024, RoHS

* Startup temperature is -10°C/12°F

Accessories

CX-PWR-12W-US	US power supply
CX-PWR-12W-EU	EU power supply

A complete list of mounts, brackets, pole mounts and recess kits for cameras can be found in the DVTEL Price List and Camera Accessory Guide.

CANADA

FLIR Systems - Canada
250 Royal Crest Court
Markham, Ontario,
Canada L3R 3S1

PH: +1 888.425.6739

BALTIMORE

901 Elkridge Landing Road
Linthicum, MD 21090
USA

www.flir.com
NASDAQ: FLIR

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2016 FLIR Systems, Inc. All rights reserved. 03/2016



General Specifications

Camera	
Image Sensor	1/3" CMOS
Sensor Resolution	1280 x 960
Scanning Mode	Progressive
Sensitivity	0.15 (color)/0.02 (BW), 0 Lux with IR illuminator ON, measured at 30 IRE
Lens Type	4 mm F2.0 Auto Iris D/N Horizontal viewing angle: 73.1°
Rotate Options	Mirror and Flip
Automatic Electronic Shutter (AES)	1.0 to 1 / 10,000 (auto)
Digital Slow Shutter (DSS)	1/1 to 1/25 or 1/30 with up to 32x sensitivity boost in color or night mode
White Balance	Auto / indoor / outdoor
Automatic Gain Control (AGC)	Auto
Back Light Compression	Yes
Iris Control	DC Auto
Wide Dynamic Range (WDR)	Digital
3D Noise Reduction	Yes
Tamper Detection	Yes
Privacy Zones	Yes
Video Motion Detection	Yes
Day / Night Mode	Yes
Mechanical IR Cut Filter	Yes
Signal to Noise Ratio (SNR)	±50 dB
Video	
Compression	Fully compliant multi-stream H.264 main profile + MJPEG
Maximum Performance	H.264 30 / 25 @ 1280x960/HD720p + H.264 30 / 25 @ 4CIF
Resolution Range	Scalable from CIF to 1.3MP
Bandwidth	Configurable between 64Kbps and 8Mbps
Rate Control	CBR/VBR
IR Illuminator	
Distance	20 m (66 ft.)
Angle of Illumination	Full 90°
Number of IR LEDs	30
Peak Emission Wavelength (nm)	850
Network	
Network Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6
Ethernet	10 / 100 Base-T auto sensing, half / full duplex (RJ45)
Configuration	Remote: via web access or supported video management software
Firmware Upgrade	Flash memory for upgrade of camera firmware over the network (1GB Flash / 2GB RAM)
Supported Web Browser	Internet Explorer 6.0+
Security	User account and password protection
Physical	
Enclosure	Indoor/Outdoor
Dimensions	60.4 x 76.9 x 139.2 mm (2.38 x 3.28 x 5.48 in.)
Unit Weight	0.5kg (1.1 lbs.)
Electrical	
Input Voltage	12 VDC ±10% or 802.3af PoE
Power Consumption	5W / 7W with IR on
Power Connector	DC barrel connector or PoE
Environmental	
Operating Temperature*	-30°C to 60°C (-22°F to 140°F)
Storage Temperature	-40° to 70° C (-4° to 158° F)
Humidity	95% (non-condensing)
Warranty & Regulatory	
Warranty	According to DVTEL RMA Policy and Process Notice document
USA	UL, FCC Part 15 (subpart B, class A)
International	CE marked, EN55022-1998 class A, EN55024, RoHS

* Startup temperature is -10°C/12°F

Camera Ordering Information

Type	Series	Camera Resolution	Included Analytics	Lens Options	Environmental	IR Illuminator
CB	30	1	1	0	1	I
Bullet Camera	30 = Ariel	1 = 1.3MP / 720p	1 = Intelligent Multi-zone VMD and Tamper Detection	0 = 4mm	1 = IP66	I = 90° Illuminator

Accessories

CX-PWR-12W-US	US power supply
CX-PWR-12W-EU	EU power supply

A complete list of mounts, brackets, pole mounts and recess kits for cameras can be found in the DVTEL Price List and Camera Accessory Guide.

